

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
26 February 2004 (26.02.2004)

PCT

(10) International Publication Number
WO 2004/016395 A2

(51) International Patent Classification⁷: **B25B**
(21) International Application Number:
PCT/US2003/025725
(22) International Filing Date: 19 August 2003 (19.08.2003)
(25) Filing Language: English
(26) Publication Language: English
(30) Priority Data:
60/404,368 19 August 2002 (19.08.2002) US
(71) Applicant and
(72) Inventor: BACULY, Eric, J. [US/US]; 7292 - 15 Mile
Road, Cedar Springs, MI 49319 (US).
(74) Agent: DOLCE, Marcus, P.; Price, Heneveld, Cooper,
Dewitt & Litton, 695 Kenmoor, S.E., P.O. Box 2567, Grand
Rapids, MI 49501-2567 (US).


(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report

[Continued on next page]

(54) Title: QUICK-CHANGE TOOLS



(57) **Abstract:** A tool having a quick-change mechanism for replacing tool implements on a shaft, post or handle comprising a shaft, post or handle having a flange and a threaded connector. The tool further includes a tool implement adapted to be received on the shaft, post or handle adjacent the flange. The tool also includes a stabilizer washer adapted to be received on the shaft, post or handle adjacent the work implement. A threaded fastener is adapted to be threaded onto the threaded connector of the shaft, post or handle whereby the tool implement and the stabilizer washer are retained on the shaft, post or handle by the fastener, and wherein the tool implement and the stabilizing washer are configured to allow removal of the tool implement without removing the fastener from the shaft, post or handle.

WO 2004/016395 A2



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.